

# DYNAPAC

Part of the Atlas Copco Group

## LP6500 (Manual) Duplex rollers



### Technical data

	LP6500 (Manual)
<b>Dimensions</b>	
Drum width	650 mm
Width	714 mm
Height	1,045 mm
Length	2,514 m
<b>Masses</b>	
Net mass	658 kg
Operating mass (CE)	696 kg
<b>Traction</b>	
Theor. gradeability	35
<b>Compaction</b>	
Static linear load	5.35 kg/ cm
Speed forward	3.60 km/ h
Speed reverse	2.30 km/ h
Vibration frequency	61 Hz
Nominal amplitude	0.45 mm
Centrifugal force	21 kN
<b>Engine</b>	
Manufacturer	Hatz
Type	1D50S
Fuel	Diesel
Rated power	6.80 kW
Rated power @	2,600 rpm
Rated power (rating standard)	SAE J1995
Fuel consumption / h	1.35 l
Fuel tank capacity	5 l
<b>Hydraulic system</b>	
Driving	Fully hydraulic
<b>Sprinkler system</b>	
Tank capacity	71 l
Type of sprinkling	Gravity



Find your local dealer at [www.dynapac.com](http://www.dynapac.com)

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.